



Ready to

REMOVE


TECHNICAL SPECIFICATIONS
BeachTech 2500




BeachTech[®]



BeachTech 2500

 **Engine power**
from 59 kW | 80 hp

 **Working width**
2.500 mm

 **Hopper volume**
2,8 m³

 **Area coverage**
up to 30.000 m²/h



Cleaning method	patented raking-/ screening-/ mixed technique	
Tractor requirements	engine power min.**	59 kW (80 hp)
	four-wheel drive	
	differential lock	
	tires	480 mm front, 520 mm back
	2-point hitch, cat. 2	
	PTO shaft	Z6, 1 3/8"
	power take-off, AR NORM	540 rpm (1000 rpm possible)
	power supply	standardized socket, 12 V
	1 double-acting circuit of the additional tractor hydraulics in standard	
	Dimensions	vehicle length, road transport
vehicle width, road transport		2.500 mm
working width		2.500 mm
vehicle height		2.250 mm
unloading height collecting hopper		2.750 mm
Tires	low pressure tires, wide (standard)	520/50 - 17
Weight	empty weight	2.790 kg
	technically permissible total weight*	4.000 kg
Tank capacity	hydraulic oil	30 l
Performance	area coverage up to**	30.000 m ² /h
Working depth	working depth up to**	30 cm
Capacity	collecting hopper	2,8 m ³
Speed	operating speed max.**	12 km/h
	road traffic*	25 / 40 km/h

* according to local traffic regulations

** depending on soil / beach conditions

dealer stamp

BeachTech®

Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com

Subject to change in the course of technical development. The images shown are for illustration purposes only and may contain optional extras.