

NEW

Ready to
REMOVE

TECHNICAL SPECIFICATIONS

BeachTech 3000
Facelift



BeachTech®

BeachTech 3000 Facelift



Engine power tractor
74 kW (100 hp)



Working width
2.500 mm



Hopper volume
4,7 m³ (total)



Area coverage
bis zu 30.000 m²/h



Cleaning method	patented raking-/ screening-/ mixed technique	
Tractor requirements	engine power min.**	74 kW (100 hp)
	four-wheel drive	
	differential lock	
	tires	500 mm front, 600 mm back
	coupling for drawbar eye Ø 40 mm, height adjustable to approx. 1 m height	
	PTO shaft	Z6, 1 3/8"
	power take-off, AR NORM	540 rpm (1000 rpm possible)
	power supply	standardized socket, 12 V
	drawbar load	1.600 kg
Dimensions	vehicle lengths, in operation	7.000 mm
	vehicle lengths, road transport	5.700 mm
	vehicle width, road transport	2.700 mm
	working width	2.500 mm
	vehicle height	2.400 mm
	vehicle height, road transport	3.950 mm
	Unloading height dump body	1.550 mm
Tires	low pressure tires, wide (standard)	500/60 - 22,5
Weight	empty weight	3.200 kg
	technically permissible total weight*	6.500 kg
Tank capacity	hydraulic oil	40 l
Performance	area coverage up to**	30.000 m ² /h
Working depth	working depth up to**	30 cm
Capacity	collecting hopper	0,7 m ³
	dump body	4,0 m ³
Speed	operating speed max.**	12 km/h
	road traffic*	40 km/h

Dealer stamp

* according to local traffic regulations

** depending on soil / beach conditions

Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com

BeachTech®