

BeachTech 2000



1,5 m³









Cleaning method	patented raking-/ screening-/ mixed technique	
Tractor requirements	Engine power min.**	55 kW (70 hp)
	Four-wheel drive	
	differental lock	
	tires	480 mm front, 520 mm back
	2-point hitch, cat. 2	
	PTO shaft	Z6,13/8"
	power take-off, AR NORM	540 rpm (1000 rpm possible)
	power supply	standardized socket, 12 V
	2 double-acting circuits of the addit	ional tractor hydraulics in standards
Dimensions	vehicle length, road transport	5.430 mm
	vehicle width, road transport	2.610 mm
	vehicle width, road transport with small tires (option)	2.300 mm
	working width	1.850 mm
	vehicle height	2.100 mm
	unloading height collecting hopper	2.600 mm
Tires	low pressure tires, wide (standard)	520/50-17
	small tires (optional)	360/70-16
Weight	empty weight	1.800 kg
	technically permissible total weight*	2.800 kg
Tank capacity	hydraulic oil	30
Performance	area coverage up to**	22.200 m ² /h
Working depth	working depth up to**	30 cm
Capacity	collecting hopper	1,5 m ³
Speed	operating speed max.**	12 km/h
	road traffic*	25 / 40 km/h

^{*} according to local traffic regulations



^{**} depending on soil / beach conditions