

NEW

Ready to  
**REMOVE**

TECHNICAL SPECIFICATIONS

**BeachTech 3000**  
**Facelift**

**BeachTech®**



# BeachTech 3000 Facelift



**Engine power tractor**  
74 kW (100 hp)



**Working width**  
8 ft 2 in



**Hopper volume**  
6.2 cu yd



**Area coverage**  
7.4 acres/hr



<b>Cleaning method</b>	patented raking-/ screening-/ mixed technique	
<b>Tractor requirements</b>	<b>engine power min.**</b>	74 kW (100 hp)
	four-wheel drive	
	differential lock	
	<b>tires</b>	19.6" front, 23.6" back
	<b>coupling for drawbar eye Ø 40 mm, height adjustable to approx. 3 ft 3 in height</b>	
	<b>PTO shaft</b>	6 spline (21 spline), 1 3/8"
	<b>power take-off, AR NORM</b>	540 rpm (1000 rpm possible)
	<b>power supply</b>	standardized socket, 12 V
	<b>drawbar load</b>	3307 lbs
<b>Dimensions</b>	<b>vehicle lengths, in operation</b>	22 ft 11 in
	<b>vehicle lengths, road transport</b>	18 ft 8 in
	<b>vehicle width, road transport</b>	8 ft 11 in
	<b>working width</b>	8 ft 2 in
	<b>vehicle height</b>	7 ft 10 in
	<b>vehicle height, road transport</b>	12 ft 11 in
	<b>Unloading height dump body</b>	5 ft 1 in
<b>Tires</b>	<b>low pressure tires, wide (standard)</b>	500/60-22,5
<b>Weight</b>	<b>empty weight</b>	7,055 lbs
	<b>technically permissible total weight*</b>	14,330 lbs
<b>Tank capacity</b>	<b>hydraulic oil</b>	10.6 US gal
<b>Performance</b>	<b>area coverage up to**</b>	7.4 acres/hr
<b>Working depth</b>	<b>working depth up to**</b>	12 in
<b>Capacity</b>	<b>collecting hopper</b>	0.9 cu yd
	<b>dump body</b>	5.3 cu yd
<b>Speed</b>	<b>operating speed max.**</b>	7.5 mph
	<b>road traffic*</b>	25 mph

Dealer stamp

\* according to local traffic regulations

\*\* depending on soil / beach conditions

Tel.: +49 7392 900 - 461  
E-Mail: [info@beach-tech.com](mailto:info@beach-tech.com)  
[www.beach-tech.com](http://www.beach-tech.com)

**BeachTech**®